

# TORCH PRO® G

## APP GRANULATED CAP SHEET

### PRODUCT DESCRIPTION

Torch Pro G is an economy grade, granular surfaced Atactic Polypropylene (APP) modified bitumen roofing membrane specially designed for heat welded applications. Constructed with APP resins, and incorporating a tough polyester reinforcement, Torch Pro G is a durable roof product that is easy to install and provides long-term weathering performance.

Torch Pro G membrane can also be used as flashing membrane in all applicable specifications, in accordance with recommended installation practices. Torch Pro G has a granulated surface and a polyolefin backing, and has good elongation properties, puncture resistance and flexibility.

### TYPICAL APPLICATIONS

- Heat-welded application
- Applied directly over an acceptable substrate or as part of a multi-ply system
- New roofing, re-roofing, re-cover and flashing details

### FEATURES AND BENEFITS

- APP formulation for ease of application and excellent weathering
- Puncture and tear resistant
- Excellent low temperature flexibility and elongation properties

### TECHNICAL DESCRIPTION

TEST METHOD	PROPERTY	ASTM VALUE
ASTM D5147	Peak Load @ 23+/-2°C (73.4+/-3.6°F), MD and XMD, min, kN/m (lbf/in.)	8.8 (50)
ASTM D5147	Elongation @ 23+/-2°C (73.4+/-3.6°F), MD and XMD, min (%)	23
ASTM D5147	Tear Strength @ 23+/-2°C (73.4+/-3.6°F), min, N (lbf)	311 (70)
ASTM E96	Low Temperature Flexibility, max, °C (°F)	0 (32)
ASTM E96	Granule Embedment, g	2

### AVAILABLE COLORS

Top surface granule protection is available in:  
 Black      Buff      White



### PRODUCT DATA

Coverage (Approx).....	100 sq ft
Weight (Approx) .....	98 lbs
Thickness (Nominal).....	4.0 mm; 160 mils
Roll Size .....	32'10" x 39 3/8" (10m x 1m)
Rolls/Pallet.....	20

### APPLICABLE STANDARDS

- ASTM D1622, Type I





**HYDRAGUARD**

# TORCH PRO<sup>®</sup> G

## APP GRANULATED CAP SHEET

### APPLICATION INSTRUCTIONS

Torch Pro G is intended to be used as the primary weathering surface in new or re-roof applications. Torch Pro G is to be applied as the outermost layer of a multi-ply roof system over a compatible base or interply sheet. Torch Pro G may be applied directly to non-combustible substrates. Always comply with applicable building code requirements.

- Apply over clean, dry, dust and debris-free substrates. Prime concrete decks prior to application with an asphalt primer.
- When re-roofing, remove all prior roofing materials down to a clean debris-free substrate and properly close-off all abandoned roof penetrations.
- Concrete or steel decks shall be designed with proper expansion devices.
- Wood decks shall have all joints blocked or properly supported and covered with appropriate base membrane.
- Ensure the fire rating of the assembly over any substrate.
- Ensure the installation of Torch Pro G does not prevent the ventilation of existing construction.
- Do not apply over shingles or any granulated surface.
- While installing Torch Pro G:
  1. Start at the low point of the roof.
  2. Unroll the material and allow to relax.
  3. Install with traditional torch roofing techniques ensuring proper heating of the roofing material as not to expose the reinforcement.
  4. Do not heat the substrate.
  5. Position successive rolls providing a minimum 6" end lap and 3" side lap. Asphalt bleed out shall be 1/4" to 3/8" on all seams.
  6. Laps shall be rolled with a 6"-wide roller immediately after heat welding.
- Details and flashing may be installed using Torch Pro G with torch applied techniques. Do not use cold adhesives or hot asphalt. Check project details for proper installation requirements.
- Use of open flame devices can cause an increased fire risk. Always have appropriate fire suppression devices handy when working with open flame. Always follow local building codes. Polyglass recommends a 2 hour fire watch when using open flame.

### MANUFACTURING FACILITIES

- Fernley, NV
- Hazleton, PA
- Phoenix, AZ
- Winter Haven, FL

### CORPORATE HEADQUARTERS

Polyglass U.S.A., Inc.

1111 West Newport Center Drive

Deerfield Beach, FL 33442

General Line: (888) 410-1375

(954) 233-1330

Customer Service: (800) 222-9782

Technical Service: (866) 802-8017

**Questions?** [technical@polyglass.com](mailto:technical@polyglass.com)

**Product Disclaimer:** Unless otherwise incorporated into or part of a supplemental manufacturer's warranty, Polyglass warrants its product(s) against manufacturing defects in its product that directly results in leakage for a period of 2 years.

*Refer to safety data sheet (SDS) for specific data and handling of our products. All data furnished refers to standard production and is given in good faith within the applicable manufacturing and testing tolerances.*

*Polyglass U.S.A., Inc., reserves the right to improve and change its products at any time without prior notice. Polyglass U.S.A., Inc. cannot be held responsible for the use of its products under conditions beyond its own control.*

*For most current product data, visit [www.hydraguardroofproducts.com](http://www.hydraguardroofproducts.com)*